


MOSCA®

EXCELLENCE IN STRAPPING SOLUTIONS



Picture with
options

KZV 111

MOSCA pallet strapping machine
to secure goods for transport.

KZV 111

MOSCA strapping machines are series-produced based on a modular principle. Sturdy design. Program-controlled integration into conveyor lines. Automatic vertical strapping. Robust single-column in modular steel sheet construction. Fully electrically-driven. Strap dispenser KA 400 for synthetic straps. With weight-neutral strap take-off and strap accumulator. Particularly suitable for automatic strapping of palletized packages. Top-mounted sealing head.

DIFFERENT MODELS

KZV-111

- Top-mounted sealing head
- One SoniXs- sealing head and one vertical strap guide
- Movable strap lance for strapping of palletized goods

KOV-111 HS

Like basic model KZV-111

- With additional underfeed channel for strapping of un palletized goods (e.g. corrugated cardboard boxes)

KVV-111

- Like basic model KZV-111
Bottom arch with automatically controlled strap lance or underfeed channel. Particularly suitable for strapping of frequently changing package types with or without pallets

STANDARD FEATURES

- Automatic height adjustment of pressure plate to bundle height
- Floating head
- Flap opener with package height scanning
- **SONIXS** ultrasonic sealing system
- Guidings of the top platen of wear-free, hardened material with appropriate guide rollers
- Modular design of top platen and machine frame in sheet metal construction
- Easy accessibility

OPTIONS:

- Strap sealing unit BSG
- Contact gibs
- Traffic light warning systems
- Air conditioning equipment
- Highspeed package

TECHNICAL DATA

CAPACITY:

up to 61 pallets/h; vertically double-strapped
– at 18 m/min conveying speed
– at package height spread $\leq \pm 200$ mm

ELECTRICAL POWER:

Operating Voltage: 400 V, 50 Hz,
3 PH / N / PE
24 V DC

Power consumption: 5.7 kW

STRAPS:

Strap Types: PP or PET straps
Strap Width: 9.5 – 12.5 mm
Strap Tension: 250 - 2,500 N
infinitely adjustable

PASSAGE WIDTH:


1,400 – 2,400 mm
in 200 mm steps

CONVEYOR HEIGHT:

0 – 650 mm adjustable

WEIGHT:

1,200 kg



* KZV-111 machine size 2000 mm
03 / 14 Subject to Alterations



MOSCA®
EXCELLENCE IN STRAPPING SOLUTIONS

MOSCA GMBH

Gerd-Mosca-Straße 1
D-69429 Waldbrunn/Germany
Tel.: +49 6274/932-0
Fax: +49 6274/932-400 118
Tel. Tech. Service: +49 6274 / 932-146
E-Mail: info@mosca.com
Internet: www.mosca.com

The models of KZV 111 are adjustable to one strap width of all quality PP or PET straps between 9.5 and 12.5 mm. Obtainable directly from Mosca, produced in one of Europe's most modern manufacturing plants. Combinable with maintenance contracts by Mosca – a one-stop solution.

